

(19)



JAPANESE PATENT OFFICE

BEST AVAILABLE COPY

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 2003174141 A

(43) Date of publication of application: 20.06.03

(51) Int. Cl.
H01L 25/065
H01L 23/12
H01L 26/07
H01L 25/18

(21) Application number: 2002237125

(22) Date of filing: 15.08.02

(30) Priority: 27.09.01 JP 2001298289

(71) Applicant: DT CIRCUIT TECHNOLOGY CO LTD

(72) Inventor: HIRAI HIROYUKI
FUKUOKA YOSHITAKA

(54) SEMICONDUCTOR DEVICE AND METHOD FOR MANUFACTURING THE SAME

COPYRIGHT: (C)2003,JPO

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a semiconductor device which assures higher reliability in the mechanical strength and moisture resistance as the semiconductor device and moreover, can improve integration degree by forming a wiring pattern to the entire part of a multi-layer plate, and also to provide a method of manufacturing the same semiconductor device.

SOLUTION: Conductor bumps 60, 60,... and so on are formed on the wiring pads 41b, 41b of a double-layer plate 52, barrier metal layer 61 and an Au layer 62 are also formed, and a semiconductor element 70 is also formed thereon. Moreover, a prepreg 31 providing an aperture 31a and another double-layer plate 54 are aligned thereon, and these are pressed under the heated condition. At the surface of the semiconductor device 1 obtained, the boundary surface of the insulation resin filling the circumference of the semiconductor element 70 and the double-layer plate 54 does not appear.

